

[0001] The invention relates to a security element, namely a bar code in the form of a watermark, as well as a security paper and a document of value or security document manufactured thereof, such as for example bank note, check, share, identity card, ticket for public transport, admission ticket and the like, with such a bar code, and furthermore a method and a papermaking screen for manufacturing the security paper.

[0002] It is known to incorporate a bar code in a paper in the fashion of a watermark, in particular in a security paper, for manufacturing security documents or documents of value. For example, the authenticity of bank notes can be tested with reference to the bar code, if all bank notes of a certain value and a certain date of issue bear a certain watermark in the same fashion. By comparing with the serial number and the denomination printed on the bank note then the authenticity of the bank note can be checked with reference to the bar code. Depending on the complexity of the information encoded in the watermark bar code, the bar code can become comparatively long, which is undesirable with small dimensioned documents of value, such as for example bank notes.

[0003] The problem, however, is not only the length of the bar code, but in particular its checkability for the purpose of determining the authenticity. Because the broader the bars incorporated as a watermark in the paper, the more irregular is their appearance on transmissive viewing. The reason for this is that a watermark with a regular dark surface can be realized only with difficulties. For manufacturing the watermark the papermaking screen is embossed, so that the deposit of paper fiber during the sheet formation is influenced. If the papermaking screen is deep-embossed, more paper pulp deposits in this area, while a high-embossing impedes the deposit of paper pulp. With an embossed surface above all the edges of the surface are reproduced well. The surface itself towards its inner area becomes either lighter or darker.

[0004] It is the problem of the present invention to propose a bar code in the form of a watermark, which is more versatile and comparatively space-saving. A further problem of the invention is to provide a security paper equipped with such a bar code

and papers of value or security documents manufactured thereof, as well as a method and a papermaking screen for manufacturing the security paper.

[0005] These problems are solved by a bar code, a security paper, a security document, a method and a papermaking screen according to the independent claims. In claims dependent on these are specified advantageous embodiments and developments of the invention.

[0006] Accordingly, the separating fields, through which the information-conveying bars are separated from each other, are formed as uniquely detectable watermarks. These separating fields are detected as (separating-field) bars by the bar-code reader. The actual bar code information, however, is not determined by the width of the detected (separating-field) bars but by the width of the fields located in between the detected (separating-field) bars, these fields representing the actual bars of the bar code. I. e., beginning and end of the information-conveying bars are each marked by the separating-field bars.

[0007] This offers the two following substantial advantages compared to prior art. Firstly, the information-conveying bars of the bar code located between the separating fields can be selected in any width. Since the lightness of the information-conveying bars is not taken into account when evaluating, there exist no problems with an irregularly filled bar surface appearing dark or light in transmitted light. Secondly, the separating fields can be formed extra narrow, in particular by using electrotypes on the papermaking screen, as a result of which the total length of the bar code is comparatively short and space-saving.

[0008] As to further reduce the length of the bar code, it is advantageous to form the bar code as a two-dimensional bar code, which has several e. g. parallel information tracks.

[0009] A particularly advantageous embodiment of the invention provides that the fields located between the separating fields, which form the actually information-conveying bars of the bar code, are not designed as a watermark, so that in transmitted light only the separating fields can be recognized as watermark bars. The first and the

last separating field define the boundaries of the bar code.

[0010] As to increase the contrast, the information-conveying bars of the bar code, too, can have the design of a watermark, the separating fields being formed as light watermarks and the information-conveying bars as dark watermarks - or vice versa -. It is preferred that not the information-conveying bars are formed as light watermarks but the separating fields, since otherwise with light information-conveying bars at increasing width of the bars there would exist a danger of formation of holes in the paper.

[0011] According to a special embodiment of the invention a separating field located at the edge of the bar code, which means a first or last separating field, for example by means of its characteristic width or its fiber density defines the information content to be assigned to the bars of different width, i.e. whether a broad bar indicates a „1“ and a narrow bar a „0“ or vice versa. Alternatively, the first bar can be defined as a startbit and its width can indicate, whether a broad bar of the bar code indicates „1“ and a narrow bar „0“ or vice versa.

[0012] According to a preferred embodiment, an inventive security document or document of value is equipped with an additional storage medium. This can be for example a magnetic storage medium, such as a magnetic track, or an electronic storage medium, such as a microchip with integrated circuits. With such an embodiment the bar code can contain data for encoding and decoding of information instead of the value of the document. In the storage medium can be stored in an advantageous fashion the document value rendered by the bar code together with the serial number of the document, or for example the result of a predetermined combining of the value factor and serial number. With that the forgery-proofness and the checkability of the authenticity of a document is increased. The storage of the combining in the additional storage medium can be effected when manufacturing the document or at the time of bringing it into circulation. When testing the authenticity the result of the combining can be read from the storage medium. If the way of combining is known, together with the document value which very easily can be read out from the bar code watermark, the serial number can be reconstructed. If in addition the serial number is read directly

from the document, a further possibility arises for checking whether a read-out storage medium really belongs to an individual document such as for example a bank note.

[0013] Furthermore, coincidences in the formation of the inventive bar code, such as the cloudiness of the paper in the bar code area or irregularities in the run of the edge of individual sections, can be used as an additional measured value, so as to increase the forgery-proofness of a document or to improve the authenticity testing.

[0014] In the following the invention is described by way of example with reference to the accompanying figures.

[0015] Figure 1 shows a bank note with an inventive watermark bar code,

[0016] Figure 2 shows a transmitted light view of an inventive watermark bar code,

[0017] Figure 3 shows a transmitted light view of a further inventive watermark bar code,

[0018] Figure 4 schematically shows a papermaking screen in cross section,

[0019] Figure 5 shows a transmitted light intensity curve according to a first embodiment of an inventive watermark bar code,

[0020] Figure 6 shows a transmitted light intensity curve according to a second embodiment of an inventive watermark bar code,

[0021] Figure 7 shows a transmitted light intensity curve according to a third embodiment of an inventive watermark bar code,

[0022] Figure 8 shows a transmitted light view of a watermark bar code according to prior art,

[0023] Figure 9 shows a transmitted light intensity curve of a watermark bar code according to prior art, and

[0024] Figure 10 shows a transmitted light intensity curve of a watermark bar code

according to a further prior art.

[0025] Figure 1 shows in an exemplary fashion as one of many possible documents of value and security documents a bank note 1 with the denomination 2 of „EUR 100“. The bank note 1 has a two-dimensional bar code 3, which is integrated in the fashion of a watermark in the security paper, out of which the bank note 1 is manufactured.

[0026] Documents of value with a one-dimensional bar code in the form of a watermark are already known from prior art. The broader the bars incorporated in the paper as a watermark, the more irregular their appearance in transmitted light, so that the evaluation of the bars is very problematic. This is shown in Figure 8, which schematically shows a watermark bar code 3 viewed in transmitted light. The bar code 3 was produced with an embossed papermaking screen, which in its embossed areas producing the bars 5 of the bar code 3 promotes the deposit of paper fiber. However, the fiber density i.e. the paper thickness, decreases towards the inner areas of the surface of the bar, so that the edge area of the surface can be imaged well, but the inner areas of the surface in transmitted light appear lighter vis-a-vis the edge areas. This is graphically shown in Figure 9, where the transmitted light intensity I^+ , I^- deviating from a normal transmitted light intensity I_0 is plotted. It can be recognized that the transmitted light intensity I in the center of the bars comes the closer to the normal transmitted light intensity I_0 the broader the bar is. Here it has to be taken into account that the normal transmitted light intensity value I_0 in Figure 9 is shown in an idealized way. Actually, this value I_0 varies about an average value, so that with broad bars it can occur that a bar code sensor signalizes the end of a bar 5 or the beginning of a separating field 6, although not more than the middle of the bar 5 has been reached. This can lead to read errors, because a broad bar 5 may be interpreted as two short bars by mistake.

[0027] The alternative, to use a light bar code instead of a dark bar code, has the same disadvantage, namely that the fiber density decreases towards the middle of the bar. Again the result is not a regularly light bar of the desired dimension. Furthermore, with broad bars there exists the danger of formation of holes in the paper.

[0028] In Figure 10 is shown the transmitted light intensity I of a bar code known

from DE 30 34 916 A1, where the problems described above do not arise. According to this the areas of the papermaking screen used for producing the bars of the bar code are embossed as rectangular, not isosceles triangles in the papermaking screen. The part of the watermark, which is produced by means of the steep edge in the paper, in transmitted light is easily recognizable as distinctive dark or light stripe and marks the beginning of a bar 5. Whether the bar 5 represents „1“ or „0“, does not depend on its width but on the fact, whether the bar is light or dark, which means whether the embossing of the papermaking screen starting from the level of the papermaking screen is directed downwards or upwards. As a result of this also the length of the whole bar code can be kept short, because separating fields 6 between the individual bars 5 for the clear delimitation from each other can be omitted. Disadvantageous, however, is the fact, that the bar code is restricted to a digital encoding, because only light and dark fields are differentiated.

[0029] The Figures 2 and 3 each show a part of the different embodiments of a watermark bar code 3 from Figure 1 according to line AA upon viewing in transmitted light. In both cases and also in the examples explained in the following, the bar code is a digital bar code consisting of zeros and ones, the width of the bar indicating the value „0“ or „1“. The bars 5 are separated from each other by separating fields 6, the first and the last separating field defining the boundaries of the bar code. The bar codes shown in Figures 2 and 3 thus each read 0-1-1-0.

[0030] With the embodiment according to Figure 2 the separating fields 6 appear dark compared to the bars 5. That means, in the areas of the separating fields 6 the bank note has an increased fiber density, which has been produced by a respective embossing of the papermaking screen used for manufacturing of bank note paper. This embossing of the papermaking screen causes an increased deposit of paper fiber during the papermaking, by means of which the transmitted light intensity, when the paper is viewed in transmitted light, is decreased respectively and the separating fields 6 appear dark. The bars 5, which define the actual information of the bar code, in transmitted light appear neither lighter nor darker than the bank note material surrounding the bar code, since the bars 5 do not have any watermark characteristics. Since due to this fact not the information-conveying bars 5 but the separating fields 6 are detected by means

of a bar code reader, the width of the information-conveying bars is determined merely indirectly via the distance between the detected separating fields 6.

[0031] The same applies to the embodiment shown in Figure 3, in which, deviating from the embodiment according to Figure 2, the separating fields 6 of the bar code appear light, except for the separating field on the extreme left. The light separating fields 6 can be produced particularly strikingly by using so-called electrotypes. Electrotypes, in general, are small metal parts, which are fixed on one side of the papermaking screen, for example soldered or by means of brackets which are put into the mesh of the screen and bent over. With that very narrow and particularly light transmitted light effects can be obtained, which are easily to detect by sensors.

[0032] The extreme left separating field 6 in Figure 3 defines that the following broad bars are to be counted as „0“ and the narrow bars 5 as „1“, as it is the case in Figure 2. If the extreme left separating field 6 would be formed as a light separating field, like all other separating fields 6, then the information content of the bars 5 would be the other way round and the whole information of the bar code would not read 0-1-1-0 but 1-0-0-1.

[0033] Instead of the characteristic transmitted light intensity or fiber density of the extreme left separating field 6 - it could also be the extreme right separating field 6 - also the width of the separating field could be related to, so as to indicate the information content of the broad and narrow bars 5. The two possibilities can also be combined, in particular as to define further information of the bar code.

[0034] Alternatively or additionally, also the first or the last bar 5 can serve as a startbit or endbit, for example, the width of the startbit bar or endbit bar giving information on whether the broad bars are counted as „0“ and the narrow bars as „1“ or vice versa.

[0035] In Figure 4 by way of example and only schematically is shown a part of a papermaking screen 8, with which a paper with a watermark bar code according to Figure 3 can be manufactured. For that the papermaking screen 8 has electrotypes 7 appropriately spaced-apart on its papermaking surface for producing the light

separating fields 6, as well as a deep-embossed area 9 for producing the extreme left separating field 6 that has an increased paper thickness or fiber density and therefore appears dark in transmitted light.

[0036] Figure 5 shows an idealized course of the transmitted light intensity of a bar code similar to that shown in Figure 2 with dark separating fields 6 and with information-conveying bars 5. The transmitted light intensity I in the areas of the separating fields 6 lies below a normal transmitted light intensity I_0 of bank note paper, since the fiber density F in the areas of the separating fields 6 is respectively high. The transmitted light intensity curve I thus coincides with the fiber density curve F , if the intensity increase I^+ is plotted upwards and the fiber density increase F^+ downwards. Transmitted light intensity curve and fiber density curve therefore are both described with reference number 4.

[0037] Figure 6 shows the curves of the transmitted light intensity and the fiber density 4 for a bar code similar to that shown in Figure 3. In this case the transmitted light intensities I in the areas of the separating fields 6 lie above the normal transmitted light intensity I_0 , except for the extreme left separating field 6, the transmitted light intensity I of which lies below the normal transmitted light intensity I_0 . In contrast to the description according to Figure 5 the transmitted light intensity curve in Figure 6 is shown in a less idealized fashion, as a result of which it becomes apparent, that the transmitted light intensity or fiber density, despite of its in general regular distribution I_0 , F_0 along the extend of the bar 5 of the bar code, slightly varies about an average value I_0 or F_0 , which indicates the „normal transmitted light intensity“ and „general fiber density“.

[0038] In Figure 7 a further embodiment of the invention is shown. Basically it is a combination of the prior art according to Figure 9 and the embodiment according to Figure 6 or Figure 3. That means, the separating fields 6 as well as the bars 5 are integrated in the paper in the fashion of a watermark, the information-conveying bars 5 in transmitted light appearing as dark areas with somewhat lighter centers, at the outset described as disadvantageous, and the separating fields 6 appearing as strikingly light lines easily to identify. The particularly high transmitted light intensity in the areas of

the separating fields 6 exceeds the transmitted light intensity in the lighter center areas of the information-conveying bars 5 in such a way, that a misinterpretation, as explained at the outset, can be ruled out. The embodiment according to Figure 7 compared to the embodiments according to the Figures 5 and 6 or 2 and 3 offers an additional increase of contrast between the areas of the bars 5 and the separating fields 6 and thus an improved readability of the bar code.